NCSPHS AMENDMENT

The Neighborhoods, Community Services, Public Health & Safety Committee offers the following amendment to File No. 2019-331:

- (1) On page 1, line 14, strike "VARIANCE" and insert "VARIANCES";
- (2) On page 1, line 18, after "SECTIONS" insert "652.1102 (SUBDIVISION PLATS),";
- (3) On page 1, lines 28-31, <u>strike</u> "SECTION 652.502 (INFORMATION IN FLOOD HAZARD AREAS WITHOUT BASE FLOOD ELEVATIONS (APPROXIMATE ZONE A)) TO ADDRESS CERTAIN FINISHED FLOOR ELEVATIONS, AND";
- (4) On page 2, line 14, after "652.501" <u>insert</u> "(INFORMATION FOR DEVELOPMENT IN FLOOD HAZARD AREAS)";
- (5) On page 4, strike lines 3-19;
- On page 6, line 7, strike "Director of the Planning and Development Department" and insert "Chief of Building Inspection, the Chief of the Engineering and Construction Management Division, and the Chief of the Development Services Division (Chiefs)";
- (7) On page 6, lines 10-11, 16-17, 21-22, and 27, strike "Director of the Planning and Development Department" and insert "Chiefs";
- (8) On page 6, lines 22-25, strike "Circuit Court, as provided by Florida Statutes Council using the procedures, timeframes, and standard of review in Section 656.135, Ordinance Code" and insert "Circuit Court, as provided by Florida Statutes";
- (9) On page 7, lines 2-3, 14-15, and 22-23, strike "Director of the Planning and Development Department" and insert "Chiefs";
- (10) On page 7, line 3, strike "has" and insert "has have";
- (11) On page 7, line 3-4, <u>strike</u> "the Director deems" and <u>insert</u> "the Chiefs deems deem";
- (12) On page 8, <u>strike</u> lines 5-10, and <u>insert</u> "*Floodway setback*. The area between the outer boundary of the regulatory floodway

associated with a natural named river or riverine watercourse shown on the FIRM and a line parallel thereto at a distance of 25 feet. The purpose of this 25-foot floodway setback is to minimize encroachments and to protect the timely discharge of the base flood taking into account the dynamic nature of natural watercourses.";

- Elevation requirements. Buildings and structures in special flood hazard areas shall have the lowest floors elevated to or above the base flood elevation plus 2 feet, or the design flood elevation, whichever is higher. In order to elevate the finished floor to this level, off-grade or stem wall construction techniques shall be used such that the lot itself is not filled more than 1 foot above base flood elevation at the site of any structure. This Section 652.1207 shall not be effective until the City of Jacksonville adopts a Local Amendment to the Florida Building Code, pursuant to Section 553.73, Florida Statutes.";
- (14) On **page 1, line 1,** amend the introductory sentence to add that the bill was amended as reflected herein.

Form Approved:

/s/ Shannon K. Eller

Office of General Counsel

Legislation Prepared By: Shannon K. Eller

GC-#1285836-v1-2019-331 NCSPHS Amd